

**Product Name:** Ultimate Polish 302

**Description:** AUTOTRIZ Ultimate Polish 302 permanently removes fine swirl marks to produce deep, wet reflections with hologram-free finish. It also adds depth of colour, especially on dark-coloured cars, & leaves the paint finish incredibly clear & glossy with mirror-like reflections.



Technical Data		General Data	
<b>Appearance</b>	Cream	<b>Product</b>	Ultimate Polish 302
<b>Cut</b>	3/10	<b>Group</b>	Polishing
<b>Gloss</b>	>10	<b>Category</b>	Alternative
<b>Speed</b>	Alternative	<b>Volume</b>	1L (AT-PC-302)
<b>Pressure</b>	Moderate	<b>Application</b>	Body Paint
<b>Abrasive effect</b>	Hologram removal	<b>Complimentary</b>	Wool/Foam Pad
<b>Specified Gravity</b>	1.20 g/cm <sup>3</sup>	<b>Industries</b>	Detailing/Paint shops
<b>Hazard</b>	Non-Hazardous	<b>Storage</b>	5-35°C/41-95°F

**Directions:** Shake bottle well before use. Work on a cool and clean surface.

DA Application: Apply product to the AUTOTRIZ Medium Cut Wool Pad (AT-WP-MC), or Medium Cut Foam Pad (AT-FP-MC), or Fine Cut Foam Pad (AT-FP-FC). Set machine speed to 4-5, Apply moderate to light pressure with 3-5 overlapping passes until desired cutting result is achieved.

Rotary Application: Set rotary polisher speed to 1500-2000RPM. Use AUTOTRIZ Heavy Cut Wool Pad (AT-WP20) or Fine Cut Wool Pad (AT-WP30). Apply product on paint surface directly, work on 2'x2' area at each time. Apply moderate to light pressure with 3-5 overlapping passes until scratches and sanding marks are removed.

Removes residue with a AUTOTRIZ Microfiber Cloth Ultrafine (AT-MT40).

**Tips:** Clean pads frequently. Use AUTOTRIZ Surface Prep (AT-CC-SP) to remove residue and check for any defect.